
Safety Data Sheet



• Index number: 603-108-00-1

3 Hazards identification

• Hazard description:



Xi Irritant

· Information concerning particular hazards for human and environment:

R 10 Flammable.

- R 37/38 Irritating to respiratory system and skin.
- R 41 Risk of serious damage to eyes.
- R 67 Vapours may cause drowsiness and dizziness.

4 First aid measures

- · After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- · After swallowing: If symptoms persist consult doctor.

5 Fire-fighting measures

- · Suitable extinguishing agents:
- CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · Protective equipment: No special measures required.

(Contd. on page 2)

(Contd. of page 1)

6 Accidental release measures

- · Person-related safety precautions: Wear protective equipment. Keep unprotected persons away.
- \cdot **Measures for environmental protection:** Do not allow to enter sewers/surface or ground water.
- *Measures for cleaning/collecting:* Dilute with plenty of water. Ensure adequate ventilation.

7 Handling and storage

- · Handling:
- Information for safe handling: No special requirement • Information about fire - and explosion protection:
- *Keep ignition sources away Do not smoke. Protect against electrostatic charges.*

· Storage:

- · Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep container tightly sealed.

8 Exposure controls/personal protection

• Additional information about design of technical facilities: No further data; see item 7.

· Ingredients with lim	it values that require monitoring at the workplace:
78-83-1 butanol	
PEL (USA)	300 mg/m³, 100 ppm
REL (USA)	150 mg/m ³ , 50 ppm
TLV(USA)	152 mg/m ³ , 50 ppm
WEL (Great Britain)	Short-term value: 231 mg/m ³ , 75 ppm
	Long-term value: 154 mg/m ³ , 50 ppm

• Additional information: The lists valid during the making were used as basis.

· Personal protective equipment:

· General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing Wash hands before breaks and at the end of work. Avoid contact with the skin.

Avoid contact with the eyes and skin.

· Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device. • Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

(Contd. on page 3)

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation \cdot **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

• *Penetration time of glove material The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.*

• Eye protection:



Tightly sealed goggles

· General Information	
Form:	Fluid
Colour:	Colourless
Odour:	Sweetish
· Change in condition	
Melting point/Melting range:	-108°C
Boiling point/Boiling range:	108°C
· Flash point:	24°C
· Ignition temperature:	390°C
Danger of explosion:	Product is not explosive. However, formation of explosive air/vapour mixture are possible.
• Explosion limits:	
Lower:	1.7 Vol %
Upper:	12 Vol %
• Vapour pressure at 20°C:	12 hPa
• Density at 20°C:	0.8016 g/cm ³
· Solubility in / Miscibility with	
water at 20°C:	100 g/l
• pH-value (80 g/l) at 20•C:	7
· Viscosity:	
Dynamic at 20°C:	3.95 mPas

10 Stability and reactivity

• Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

- · Dangerous reactions No dangerous reactions known.
- · Dangerous decomposition products: No dangerous decomposition products known.

(Contd. of page 2)

(Contd. on page 4)

11 Toxicological information

· Acute toxicity:

· LD/LC50 values relevant for classification:

Oral LD50 2460 mg/kg (rat)

Dermal LD50 3400 mg/kg (rabbit)

- · Primary irritant effect:
- on the skin: Irritant to skin and mucous membranes.
- on the eye: Strong irritant with the danger of severe eye injury.
- · Sensitization: No sensitizing effects known.

12 Ecological information

· General notes:

Water hazard class 1 (German Regulation) (Assessment by list): slightly hazardous for water Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

13 Disposal considerations

- · Product:
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· Uncleaned packaging:

• Recommendation: Disposal must be made according to official regulations.

14 Transport information

· Land transport ADR/RID (cross-border)



· ADR/RID class:	3 Flammable liquids.
· Danger code (Kemler):	· 30
· UN-Number:	1212
• Packaging group:	III
· Hazard label:	3
· Description of goods:	1212 ISOBUTANOL (ISOBUTYL ALCOHOL)
· Maritime transport IM	DG:
· IMDG Class:	3
· UN Number:	1212
· Label	3
· Packaging group:	III
	(Contd. on page 5)

(Contd. of page 3)

(Contd. of page 4)

EMS Number:	F-E,S-D
Marine pollutant:	No
	e: ISOBUTANOL (ISOBUTYL ALCOHOL)
Air transport ICAO-1	TI and IATA-DGR:
3	
ICAO/IATA Class	3
	3 1212
UN/ID Number:	3 1212 3
ICAO/IATA Class: UN/ID Number: Label Packaging group:	1212

15 Regulatory information

· Labelling according to EU guidelines:

The product has been classified and marked in accordance with EU Directives / Ordinance on Hazardous Materials.

· Code letter and hazard designation of product:



Xi Irritant

· Risk phrases:

- 10 Flammable.
- 37/38 Irritating to respiratory system and skin.
- 41 Risk of serious damage to eyes.
- 67 Vapours may cause drowsiness and dizziness.

· Safety phrases:

- 2 Keep out of the reach of children.
- 7/9 Keep container tightly closed and in a well-ventilated place.
- 13 Keep away from food, drink and animal feedingstuffs.
- 26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Department issuing MSDS: Product safety department

· Contact:

Mr. Menon

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)

ICAO: International Civil Aviation Organization

(Contd. on page 6)

ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO) EINECS: European Inventory of Existing Commercial Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) GefStoffV: Gefahrstoffverordnung (Ordinance on Hazardous Substances, Germany) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent (Contd. of page 5)